Digital Color Laser Printer



SP C830DN SP C831DN



Fast and efficient colour laser printers

The SP C830DN/SP C831DN are fast, user-friendly, colour A3 laser printers that are ideal in a busy office environment. They are easy to operate via a large 4.3-inch colour touch panel. Heavyweight paper up to 300 g/m² is handled in a particularly smooth and reliable way. Powered by Ricoh's next-generation controller, they give you outstanding security, a low total electricity consumption, and comprehensive device management capabilities.

- 45/55 A4 pages per minute.
- 4.3-inch colour touch panel.
- IC card authentication for increased security.
- Attractively designed.
- ECO Night Sensor reduces electricity consumption.

New fusing system

Enjoy ecological benefits and print quality improvements thanks to Ricoh's Quick Start Up Direct Heating (QSU-DH) fusing system. The device has a thin fusing belt around the heater, which reduces electricity consumption and shortens recovery time. Furthermore, fusing is done on a plane surface, reducing damage or wrinkles to papers. This leads to particularly high-quality envelope printing.



ECO Night Sensor

The innovative ECO Night Sensor further reduces the already low electricity consumption of these devices. The SP C830DN/SP C831DN can be set so that the main power shuts down when the light levels in the room dip below a certain level. The sensor detects both the decline of natural and artificial light. You can set the sensor to activate between 5 and 120 minutes after darkness falls.



Confidentiality ensured

Prevent potential information leaks should a printout be forgotten to be picked up, or picked up by mistake, by restricting the use of the SP C830DN/SP C831DN to holders of a card with an Integrated Chip (IC). IC card authentication also reduces paper output by enabling you to choose the jobs you want to print.



High productivity

The SP C830DN has a warm-up time of less than 29 seconds and prints 45 A4 pages per minute. Its first print is available after 3.7 seconds (B/W) or 5.7 seconds (colour). The SP C831DN's warm-up time is less than 25 seconds and it prints 55 A4 pages per minute. Its first print is produced after 3.4 seconds (B/W) or 5.1 seconds (colour).



Flexible printing

A USB/SD slot enables casual users to print easily from flash drives and memory cards. Further enhancements include enabling a preview screen before printing, a greater number of available print settings, and multiple selection of PDF or TIFF files.



Essential capabilities for smooth business operations



- 1 Easy access & intuitive operation via 4.3-inch colour touch panel.
- USB/SD slot to enable easy printing from flash drives and memory cards.
- 4-bin mailbox for easy separation and collection of prints.
- 4 Standard 2 x 550-sheet paper trays to stay productive at all times.
- 5 Standard 100-sheet bypass tray to take advantage of a wide range of paper sizes and types.

- Optional 2 x 550-sheet paper trays or 2 x 1,000-sheet large capacity tray for a choice of multiple paper sources.
- 7 1,200-sheet side large capacity tray to increase your productivity.
- 2,000-sheet booklet finisher & several punch kits for an entire range of finishing possibilities.

SP C830DN / SP C831DN

MAIN SPECIFICATIONS

GENERAL

SP C830DN

Technology:

Warm-up time:

First output speed:

Print speed: CPU:

Memory: HDD.

Dimensions (W x D x H):

Weight:

Power source: Duty cycle:

SP C831DN

Technology: Warm-up time:

First output speed:

Print speed: CPU: Memory:

HDD: Dimensions (W x D x H):

Weight: Power source: Duty cycle:

Printer language:

Print resolution:

Fonts:

Interface:

Network protocol:

Windows® environments:

Laser 29 sec or less

BW: 3.7 sec or less Colour. 5.7 sec or less

45ppm (A4) Celeron-M 600MHz Std: 512 MB 1.5 GB Max:

Opt.

670 x 684 x 640 mm

97kg or less

220 - 240 V, 50/60 Hz 200,000 prints per month

Laser

25 sec or less

BW. 3.4 sec or less Colour: 5.1 sec or less

55ppm (A4) Celeron-M 1.0GHz Std: 512 MB Max.

1.5 GB 250GB

670 x 684 x 640 mm 97kg or less 220 - 240 V. 50/60 Hz

200,000 prints per month

PRINTER

Std: PCL5c/6, PostScript3, PDF direct print, Mediaprint (JPEG/TIFF), PictBridge, IPDS Opt.:

1200/600/300dpi

Std: PCL:45 fonts + International

Fonts 13 fonts, PostScript3/ PDF: 136 fonts

IPDS: 108 fonts Opt.:

USB2.0, USB Host, Ethernet (100BASE-TX/10BASE-T)

IEEE1284/ECP. IEEE802.11a/b/g, Gigabit

Ethernet

TCP/IP (IPv6), IPX/SPX (option) Windows XP/ Vista/ Server 2003/

Std:

Opt.:

Server 2008/7 (32/64bit) Windows Server2008R2 (64bit) CPS-4.5 (32/64bit)/ XenApp 5.0 (32/64bit), 6.0 (32/64bit)

Mac OSX(Native), 10.2-107 or later

PAPER HANDLING

A3, A4, A5, B4, B5, DLT, Paper sizes: Std:

Legal, LT, Executive. Custom: Foolscap, Government LG,

Folio, F/GL, Eng Quatro, Com10, C5, 8K, 16K, 11" x 15", 10" x 14" 4,400 sheets

Paper input capacity: Max: Paper output capacity: Max: 4,000 sheets Paper weight: Std: 52-256g/m2 52-256g/m2 Opt: SideLCT: 60-256g/m2

Bypass: 52-300g/m2 Duplex: 52-169g/m2

SECURITY

Windows® authentication Authentication:

LDAP authentication Basic authentication User code authentication 802.1.x wired authentication

ECOLOGY

Max: 1,700 W Power consumption:

Sleep: 1.6 W

OPTIONS

1 x 550-sheet paper tray 2 x 550-sheet paper tray 2,000 sheet LCT 1.200 sheet LCT

2,000 sheet booklet finisher 3,000 sheet finisher 4bin mailbox

Bridge unit Punch unit for 3000 sheet finisher

Jogger unit **IPDS** VM Card 512MB Memory 1GB Memory NetWare option Gigabit ethernet PictBridge HDD

IEEE802.11a/g IFFF1284

CONSUMABLES

20,000 prints Toner capacity: Black:

16,000 prints Cyan: Magenta: 16,000 prints 16,000 prints Yellow:

Declared yield value in accordance with ISO/IEC 19798 Chart.

For availability of models, options and software, please consult your local Ricoh supplier.

RICOH

BIZCOPIER SOLUTIONS SDN BHD (1031323-P)

No. 17, Jalan Pekan Baru 30A / KU01, 41050 Klang, Selangor Darul Ehsan.

Tel: 03-3341 6296 imagine. change. Fax: 03-3359 6296

Email: ask@bizcopier.com.my

SPC20130107-01

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467 Phone: +65 6830 5888, Fax: +65 6830 5830

















